



Notes:

1. Raceway of inner & outer ring induction hardened. hardness: 55~62HRC
Depth ≥ 3.5mm
2. Inner & outer ring quenched & tempered, hardness: 207~262HB

Gear Data				Design		Check		Model				Weight																							
Module	m	Gear heat treatment requirements		Date		Approve		110.28.800				170Kg																							
Teeth no	z	HRC		Qty	Size	Axial clearance	0.02~0.04	Name				Scale																							
Teeth pressure angle	α	Precision(GB10095-88)		Inner ring mounting hole	30	Φ22	Radial clearance	0.02~0.04	Slewing Bearing				Qty																						
Modification coefficients	x			Outer ring mounting hole	30	Φ22	Material				Total 1 page																								
Reduction coefficients	km			Oil hole	6	M10×1	50Mn				The 1st page																								
Pitch diameter	d							Technical processing standards without notes according to ...JB/T2300-2011																											
				T:Pulg location S:Soft zone Y:Oil hole Z:Lifting hole				<p>machine tolerances without notes</p> <table border="1"> <tr> <td>≤200</td> <td>≤500</td> <td>≤710</td> <td>≤1120</td> </tr> <tr> <td>±0.30</td> <td>±0.40</td> <td>±0.50</td> <td>±0.65</td> </tr> <tr> <td>≤1600</td> <td>≤2000</td> <td>≤2500</td> <td>≤3150</td> </tr> <tr> <td>±0.80</td> <td>±0.95</td> <td>±1.10</td> <td>±1.35</td> </tr> <tr> <td>≤4000</td> <td>≤5000</td> <td></td> <td></td> </tr> <tr> <td>±1.65</td> <td>±2.0</td> <td></td> <td></td> </tr> </table>				≤200	≤500	≤710	≤1120	±0.30	±0.40	±0.50	±0.65	≤1600	≤2000	≤2500	≤3150	±0.80	±0.95	±1.10	±1.35	≤4000	≤5000			±1.65	±2.0		
≤200	≤500	≤710	≤1120																																
±0.30	±0.40	±0.50	±0.65																																
≤1600	≤2000	≤2500	≤3150																																
±0.80	±0.95	±1.10	±1.35																																
≤4000	≤5000																																		
±1.65	±2.0																																		
<p style="text-align: center;">XUZHOU WANDA SLEWING BEARING CO.,LTD</p> <p style="text-align: center;">XZWD <small>®</small> Fax: +86 516 83309366 Fax: +86 516 83915766 http://www.slew-bearing.com</p>																																			